

Solis

**THE TOUGHEST
PERFORMER
FOR YOUR FIELD**

**26
SHUTTLE XL**



**INTEGRATED
LOADER
JOYSTICK (OPTIONAL)**

**MULTI TIRE OPTIONS
(AGRI, INDUSTRIAL
& TURF TYRE)**

**QUICK ATTACHED
LOADER**

**SYNCHROMESH
SHUTTLE**

**9 FORWARD
X 9 REVERSED GEAR**



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**

THE TOUGHEST
PERFORMER
« FOR YOUR FIELD »

26
SHUTTLE XL

Solis



FEATURES	26 SHUTTLE XL
ENGINE	
Engine Type	Mitsubishi 3-Cylinder Diesel Motor
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	9 Forward + 9 Reverse
Front Axle	4WD
Transmission	Constant Mesh with Synchromesh Shuttle Lever
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21,46 @2760 fly up
Minimum Speed (Km/Hr)	1,14@rated
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
Trailer load (unbraked)	1050 Kg
Inertia Braked	3000 Kg
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540/540E
PTO (actuation)	Mechanical
STEERING	
Steering	Power steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DA
Hydraulic Lifting Capacity	600 Kg
Lift Rods	Standard
Litre per Minute(LPM)	17.8

FEATURES	26 SHUTTLE XL		
SAFETY SWITCH			
PTO Safety	Standard		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
CAPACITY (LTRS)(+/-5%)			
Fuel Tank (Lit)	20		
TURNING RADIUS			
Without brakes (m) as per standard tyres	3.02 (RHS), 3.15 (LHS)		
TYRE			
Front	6.00-12		
Rear	8.30-20		
DIMENSION & WEIGHT(+/-5%)			
Weight (Kg)	1250		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (max)-1050 (min)		
Height (mm) Up to ROPS	2325		
Min Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	960		
OTHERS			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with std. Ballast	Front weights-2 x 15		
Trailer Hitch	Towbar, drawbar (optional)		
ROPS	Yes		
OPTIONAL FEATURES			
Cabin Option	Yes		
Tyres			
Radial Agri: Front Rear 6,5/80-12 280/70 R18	Turf: Front Rear 25x8,50-14 13.60-16	Ind: Front Rear 23x8,50-12 33x15,50-16,5	GALAXY PRO R- 280/70R16
Front loader	YES optional		

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

NORTH EAST GARDEN MACHINERY
UNIT 16 PEARSONS IND. ESTATE
HETTON LE HOLE
TYNE AND WEAR
DH50BG www.negm.co.uk
01915269209 sales@negm.co.uk

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220 / 522222
Fax: 91- 01882-522222 | Email: exports@sonalika.com | URL: www.solistractors.com/www.solisworld.com